

DRAG FINISHERS

All advantages at a glance

- ▶ Ideal for high-quality, delicate, and complex work pieces
- ▶ Up to 40-fold higher processing intensity than vibratory systems
- ▶ Intelligent process control enables reproducible results
- ▶ Combinable process steps (e.g., pre-grinding, fine grinding, and polishing)
- ▶ Automation and integration into production cells possible
- ▶ Also suitable for large/heavy components



Model range:	R 4/700 SF	R 4/700 SF.2	R 6/1000 SF
Number of work stations	4	4	6
Number of work bowls	1	2	1
Work bowl diameter (mm)	700	700	1,080
Installed electrical load (kW)	9	9	12.5
Overall dimensions (L x W x H) (m)	2.1 x 1.5 x 2.6	3.4 x 1.5 x 2.6	2.3 x 1.9 x 2.8

Additional specifications available upon request

Model range:	R 2/800 SF-A	R 3/800 SF-A	R 4/800 SF-A	R 4/1000 SF-A	R 6/1000 SF-A
Number of work stations	2	3	4	4	6
Number of work bowls	1	1	1	1	1
Work bowl diameter (mm)	800	800	800	1,080	1,080
Installed electrical load (kW)	9	11	13	13	14
Overall dimensions (L x W x H) (m)	2.1 x 1.9 x 3.4	2.1 x 1.9 x 3.4	2.1 x 1.9 x 3.4	2.3 x 2.4 x 3.5	2.3 x 2.4 x 3.5

Additional specifications available upon request

Model range:	R 4/1300 SF	R 4/1300.2 SF
Number of work stations	4	4
Number of work bowls	1	2
Work bowl diameter (mm)	1,280	1,280
Installed electrical load (kW)	23	23
Overall dimensions (L x B x H) (m)	2.5 x 3.2 x 2.5	6.5 x 3.5 x 2.5

Additional data available upon request