





TUB VIBRATORS

All advantages at a glance

- ▶ Ideal solution for long or bulky work pieces
- ▶ Can be used for almost all mass finishing processes
- ▶ Individual processing or batch operation possible
- ▶ Work bowl can be divided into individual compartments
- ▶ Efficient operation thanks to flange-mounted drive units
- ▶ Time and cost savings thanks to automatic loading and unloading



Tub vibrators, model range TE-30	Type A	Type B	Drive speed	Dimensions (mm)							Volume	Volume	Drive power
				3,000 RPM	Work bowl with lining				Complete machine			Type A	
			„super speed“	A	A ₁	B	C	D	E	F	Work bowl (l)	Work bowl (l)	(kW)
R 300/600	•	•	•	300	240	420	600	890	480	1.070	70	40	1,3
R 360/870	•	-	•	360	-	440	870	1.160	520	1.050	120	-	2,2

Tub vibrators, model range TE-15	Type A	Type B	Drive speed	Dimensions (mm)							Volume	Drive power
				1,500 RPM	Work bowl with lining				Complete machine			
				A	A ₁	B	C	D	E	F	(Type B)	Work bowl (l)
R 300/600	•	•	•	300	240	420	600	890	480	1.070	70 (40)	0,9
R 360/870	•	-	•	360	-	440	870	1.160	520	1.050	120	1,6
R 400/1200	•	-	•	400	-	490	1.200	1.340	640	1.280	210	1,6
R 430/1100	•	-	•	430	-	540	1.100	1.300	680	1.260	230	1,6
R 500/1000	•	-	•	500	-	580	1.000	1.200	710	1.200	260	2,2
R 500/1500	•	-	•	500	-	580	1.500	1.780	800	1.345	390	2,5
R 500/1750	•	-	•	500	-	620	1.750	1.920	850	1.340	490	3,6
R 580/1100	•	-	•	580	-	640	1.100	1.370	855	1.415	360	1,6
R 600/1000	•	-	•	600	-	680	1.000	1.200	940	1.315	360	2,5
R 650/1500	•	-	•	650	-	730	1.500	1.700	1.030	1.510	640	6,0
R 670/1950	•	-	•	670	-	650	1.950	2.230	1.010	1.470	750	6,0
R 750/1200	•	-	•	750	-	800	1.200	1.420	1.170	1.570	640	7,5
R 800/1500	•	-	•	800	-	850	1.500	1.740	1.195	1.590	910	7,5
R 910/1200	•	-	•	910	-	970	1.200	1.470	1.325	1.710	950	7,5



Tub vibrators, model range Minor		Drive speed	Dimensions (mm)							Volume	Drive power
		3,000 RPM	Work bowl with lining				Complete machine				
		„super speed“	A	A ₁	B	C	D	E	F	Work bowl (l)	(kW)
R 180/530 TE-30	•	•	180	120	230	530	650	360	615	10	0,6
R 210/530 TE-30	•	•	210	150	270	530	660	330	710	20	0,6



Tub vibrators, model range RMO		Drive speed	Dimensions (mm)							Volume	Drive power
		3,000 RPM	Work bowl with lining				Complete machine				
		„super speed“	A	A ₁	B	C	D	E	F	Work bowl (l)	(kW)
RMO 180/530 TE-30	•	•	180	120	230	530	1.250	485	960	10	0,6
RMO 210/530 TE-30	•	•	210	150	270	530	1.250	525	985	20	0,6

Tub vibrators, model range TS-30		Drive speed	Dimensions (mm)						Volume	Drive power
		3,000 RPM	Work bowl with lining			Complete machine				
		„super speed“	A	B	C	D	E	F	Work bowl (l)	(kW)
R 250/1150	•	•	250	400	1.150	2.710	600	955	100	2 x 3,0
R 300/1200	•	•	300	400	1.200	2.730	550	950	130	2 x 3,0
R 400/1200	•	•	400	480	1.200	2.910	640	1.080	210	2 x 4,0
R 500/800	•	•	500	580	800	2.355	715	1.130	210	2 x 4,0
R 500/1000	•	•	500	580	1.000	2.590	715	1.020	260	2 x 4,0

Tub vibrators, model range TSD	Type A		Drive speed	Dimensions (mm)						Volume	Drive power
			1,500 RPM	Work bowl with lining			Complete machine				
				A	B	C	D	E	F	Work bowl (l)	(kW)
R 425/2700	•	•	425	540	2.700	4.240	715	1.370	560	2 x 4,0	
R 550/2200	•	•	550	670	2.200	3.730	900	1.470	730	2 x 4,0	
R 600/2000	•	•	600	680	2.000	3.550	950	1.380	730	2 x 4,0	
R 600/3000	•	•	600	680	3.000	4.570	950	1.210	1.100	2 x 7,5	
R 750/3000	•	•	750	810	3.000	4.580	1.120	1.210	1.640	2 x 15	
R 800/2000	•	•	800	810	2.000	3.700	1.180	1.595	1.150	2 x 7,0	
R 800/2200	•	•	800	810	2.200	3.840	1.180	1.385	1.270	2 x 15,0	
R 800/3000	•	•	800	810	3.000	4.620	1.180	1.490	1.730	2 x 15,0	
R 1000/1500	•	•	1.000	1.050	1.500	3.180	1.360	1.465	1.410	2 x 15,0	
R 1000/3000	•	•	1.000	1.050	3.000	4.620	1.380	2.115	2.820	2 x 15,0	
R 1100/2000	•	•	1.100	1.050	2.000	3.560	1.455	2.180	2.050	2 x 15,0	
R 1200/2300	•	•	1.200	1.300	2.300	3.960	1.600	1.755	3.230	2 x 15,0	
R 1300/2000	•	•	1.300	1.150	2.000	3.600	1.690	1.935	2.620	2 x 15,0	

Tub vibrators, model range TUD	Type A	Type B		Drive speed	Dimensions (mm)						Volume	Volume	Drive power
				1,500 RPM	Work bowl with lining				Complete machine		Type A	Type B	
					A	A ₁	B	C	D	E	F	Work bowl (l)	Work bowl (l)
R 425/4600	•	•	•	425	330	520	4.600	5.115	1.420	1.580	920	650	18,0
R 425/6600	•	•	•	425	330	520	6.600	7.115	1.460	1.600	1.330	930	18,0
R 550/4000	•	•	•	550	430	650	4.000	4.900	1.370	1.700	1.300	950	22,0

Tub vibrators, model range TUM	Type A	Type B	Drive speed	Dimensions (mm)								Volume	Volume	Drive power
				1,500 RPM	Work bowl with lining				Complete machine				Type A	
			A		A ₁	B	C	D	E	F	work bowl (l)	work bowl (l)	(kW)	
R 1500/3300	•	-	•	1.500	-	1.360	3.300	3.860	1.965	2.195	5.930	-	40,0	

Tub vibrators, model range TU	Type A	Type B	Drive speed	Dimensions (mm)								Volume	Volume	Drive power
				3,000 RPM „super speed“	Work bowl with lining				Complete machine				Type A	
			A		A ₁	B	C	D	E	F	Work bowl (l)	Work bowl (l)	(kW)	
R 350/4000	•	•	•	350	295	440	4.000	5.530	780	1.275	560	380	18,5	

- A - Width work bowl, Type A
- A₁ - Width work bowl, Type B
- B - Height work bowl
- C - Length work bowl
- D - Total length machine
- E - Total width machine
- F - Hight machine